



008 Series Powered Respirator - PAPR



FS008



LED STATUS INDICATOR



Running steadily / Battery indicator



High temperature / Filter blocking / Low battery



Over current or voltage /Unit halt

Product features

- 3 Selectable Air Flow Rates
- HD LCD Display Screen
- Multiple operating languages available

- Smart filter recognition to track usage
- High capacity battery offers 16 working hours at air flow level 1
- Protection class IP54 increases to IP67 with cleaning kit

HD LCD Display



Exploded View



008 Series Powered Respirator – PAPR

SPECIFICATIONS

1. IP Rating	IP54 in use, IP67 storage with cleaning kit
2. Airflow	Level 1: >170L/min Level2: 190L/min Level 3: 210L/min
3. System	Automatic detecting and controlling system constantly provides stable clean air
4. Switch	ON/OFF: 3 levels of airflow control Menu: Switch between different menu Enter: Select
5. Interaction Interface	LCD digital display
6. Warning	Color screen LCD display; Audible; Vibration; Running LED light; Low battery, Jammed filter, High temp battery; Gas filter service life
7. Working Noise	Max.70dB
8. HE Filter Efficiency	Particle 99.996% @0.185 um
9. Protect Level	AS/NZS 1716:2012 PAPR P3 CE: A1/A1B1E1K1 TH3;
10. Battery Life	Standard battery(12V 4500mAh) Level 1: >8h Level 2: >6h Level 3: >4h Heavy duty battery(12V 9000mAh) Level 1: >16h Level 2: >12h Level 3: >8h
11. Battery	Standard battery: LI-ION 12V 4500 mAh Heavy duty battery (optional) : LI-ION 12V 9000 mAh
12. Charging Time	Standard battery: 3.5H Heavy duty battery: 7H
13. Charging Frequency	>500
14. Operating Temperature	-15°C - 55°C (5°F - 149°F)
15. Certification	AS/NZS 1716:2012 CE EN12941; GB30864

ASSEMBLY AND SPARE PARTS



Optional Spare Parts



169 Berkeley Road Unanderra NSW 2526
1300 533 537
sales@alltradesgroup.net.au